





技术参数	TECHNICAL DATA	单位 UNITS	参数值 PARAMETER VALUE
额定斗容量	Lood bucket capacity	m <sup>3</sup>	1
额定装载质量	Rated loading mass	kg	1600
最大掘起力	Break out force	kN	49
最大牵引力	Maximum tractive force	kN	38
倾翻载荷	Tipping load	kN	32
前进一档	Travel speed in forward 1 <sup>st</sup>	km/h	0-11
前进二档	Travel speed in forward 2 <sup>nd</sup>	km/h	0-27
后退一档	Travel speed in reverse 1 <sup>st</sup>	km/h	0-10
后退二档	Travel speed in reverse 2 <sup>nd</sup>	km/h	0-26
卸载高度(H)	Dump height	mm	2600
最大卸载高度时的卸载距离	Reach fully raised	mm	880
挖掘斗容量	Hoe bucket capacity	m <sup>3</sup>	0.2-0.3
最大挖掘深度	Maximum digging depthk	mm	4100
最大挖掘半径	Maximum digging radius	mm	5000
动臂回转角度	Boom rotation angle	°	180
发动机型号	Engine model		4102BG或4102GB
标定功率	Engine rated power	kw	50
标定转速	Engine rated revolutions per minute	r/min	2400
最大转向角(左右)	Engine articulation angle(Left/Right)	°	35
最大爬坡能力	Maximum climbing ability	%	45
最小转弯半径(前轮中心)	Minimum turning radius,(The center of the forward wheel)	mm	4190
整机操作质量	Operating mass	kg	6400
外型尺寸(长X宽X高)	Overall dimension(L×W×H)	mm	6690×2060×3273

敬告：请选用我公司和我公司指定配件经销点的正宗配件。



若技术变化，不另行通知 The technical data may be changed without notice