


Wire Rope 16xK7+IWR



公称直径 Nominal Diameter (mm)	近似重量 Calculated mass (kg/100 m)	公称抗拉强度 Norminal tesnile Strength (MPa)				
		1570	1670	1770	1870	1960
		钢丝绳最小破断拉力 Min. Breaking load (kN)				
20	204	257	274	290	307	321
22	247	312	331	351	371	389
24	294	371	394	418	442	463
26	345	435	463	491	518	543
28	400	505	537	569	601	630
30	459	579	616	653	690	723
32	522	659	701	743	785	823
34	590	744	792	839	886	929
36	661	834	887	941	994	1040
38	736	930	989	1050	1110	1160
40	816	1030	1100	1160	1230	1290
42	900	1140	1210	1280	1350	1420
44	987	1250	1330	1400	1480	1560
46	1080	1360	1450	1540	1620	1700
48	1180	1480	1580	1670	1770	1850
50	1280	1610	1710	1810	1920	2010
52	1380	1740	1850	1960	2070	2170
54	1490	1880	2000	2120	2240	2340
56	1600	2020	2150	2280	2400	2520
58	1720	2170	2300	2440	2580	2700
60	1840	2320	2460	2610	2760	2890

Note: All Specifications are approximate. Specifications are subject to change without notice.