


Wire Rope 1x37



公称直径 Nominal Diameter (mm)	近似重量 Calculated mass (kg/100 m)	公称抗拉强度 Norminal tesnile Strength (MPa)			
		1570	1670	1770	1870
		钢丝绳最小破断拉力 Min. Breaking load (kN)			
1.4	0.98	1.51	1.60	1.70	1.80
2.1	2.21	3.39	3.61	3.82	4.04
2.8	3.93	6.03	6.45	6.80	7.18
3.5	6.14	9.42	10.0	10.6	11.2
4.2	8.84	13.6	14.4	15.3	16.2
4.9	12.0	18.5	19.6	20.8	22.0
5.6	15.7	24.1	25.7	27.2	28.7
6.3	19.9	30.5	32.5	34.4	36.4
7	24.5	37.7	40.1	42.5	44.9
7.7	29.7	45.6	48.5	51.4	54.3
8.4	35.4	54.3	57.7	61.2	64.7
9.1	41.5	63.7	67.8	71.8	75.9
9.8	48.1	73.9	78.6	83.3	88.0
10.5	55.2	84.8	90.2	95.6	101
11	60.6	93.1	99.0	105	111
12	72.1	111	118	125	132
12.5	78.3	120	128	136	143
14	98.2	151	160	170	180
15.5	120	185	197	208	220
17	145	222	236	251	265
18	162	249	265	281	297
19.5	191	292	311	330	348
21	221	339	361	382	404
22.5	254	389	414	439	464

Note: All Specifications are approximate. Specifications are subject to change without notice.