

Wire Rope 1x7



公称直径 Nominal Diameter (mm)	近似重量 Calculated mass (kg/100 m)	公称抗拉强度 Norminal tesnile Strength (MPa)			
		1570	1670	1770	1870
		钢丝绳最小破断拉力 Min. Breaking load (kN)			
0.6	0.19	0.31	0.32	0.34	0.36
1.2	0.75	1.22	1.30	1.38	1.45
1.5	1.17	1.91	2.03	2.15	2.27
1.8	1.69	2.75	2.92	3.10	3.27
2.1	2.30	3.74	3.98	4.22	4.45
2.4	3.01	4.88	5.19	5.51	5.82
2.7	3.80	6.18	6.57	6.97	7.36
3	4.70	7.63	8.12	8.60	9.09
3.3	5.68	9.23	9.82	10.4	11.0
3.6	6.77	11.0	11.7	12.4	13.1
3.9	7.94	12.9	13.7	14.5	15.4
4.2	9.21	15.0	15.9	16.9	17.8
4.5	10.6	17.2	18.3	19.4	20.4
4.8	12.0	19.5	20.8	22.0	23.3
5.1	13.6	22.1	23.5	24.9	26.3
5.4	15.2	24.7	26.3	27.9	29.4
6	18.8	30.5	32.5	34.4	36.4
6.6	22.7	36.9	39.3	41.6	44.0
7.2	27.1	43.9	46.7	49.5	52.3
7.8	31.8	51.6	54.9	58.2	61.4
8.4	36.	59.8	63.6	67.4	71.3
9	42.3	68.7	73.0	77.4	81.8
9.6	48.1	78.1	83.1	88.1	93.1
10.5	57.6	93.5	99.4	105	111
11.5	69.0	112	119	126	134
12	75.2	122	130	138	145

Note: All Specifications are approximate. Specifications are subject to change without notice.