


### Wire Rope 34x7+FC



**Characteristics:** 3 layer of strands, rotation resistant, regular or lang lay, right hand or left hand.

钢丝绳公称直径 Nominal rope diameter (mm)	参考重量 Approx. weight (kg/100m)		钢丝绳公称抗拉强度 Rope grade (MPa)									
			1570		1670		1770		1870		1960	
	纤维芯 FC	钢芯 WC	钢丝绳最小破断拉力 Minimum breaking load (kN)									
			纤维芯 FC	钢芯 WC	纤维芯 FC	钢芯 WC	纤维芯 FC	钢芯 WC	纤维芯 FC	钢芯 WC	纤维芯 FC	钢芯 WC
16	99,8	110	124	128	132	136	140	144	147	152	155	160
18	126	139	157	162	167	172	177	182	187	193	196	202
20	156	172	193	200	206	212	218	225	230	238	241	249
22	189	208	234	242	249	257	264	272	279	288	292	302
24	225	248	279	288	296	306	314	324	332	343	348	359
26	264	291	327	337	348	359	369	380	389	402	408	421
28	306	337	379	391	403	416	427	441	452	466	473	489
30	351	387	435	449	463	478	491	507	518	535	543	561
32	399	440	495	511	527	544	558	576	590	609	618	638
34	451	497	559	577	595	614	630	651	666	687	698	721
36	505	557	627	647	667	688	707	729	746	771	782	808
38	563	621	698	721	743	767	787	813	832	859	872	900
40	624	688	774	799	823	850	872	901	922	951	966	997
42	688	759	853	881	907	937	962	993	1020	1050	1060	1100
44	755	832	936	967	996	1030	1060	1090	1120	1150	1170	1210
46	825	910	1020	1060	1090	1120	1150	1190	1220	1260	1280	1320
48	899	991	1110	1150	1190	1220	1260	1300	1330	1370	1390	1440
50	975	1080	1210	1250	1290	1330	1360	1410	1440	1490	1510	1560
52	1050	1160	1310	1350	1390	1440	1470	1520	1560	1610	1630	1690
54	1140	1250	1410	1460	1500	1550	1590	1640	1680	1730	1760	1820
56	1220	1350	1520	1570	1610	1670	1710	1770	1810	1860	1890	1950
58	1310	1450	1630	1680	1730	1790	1830	1890	1940	2000	2030	2100
60	1400	1550	1740	1800	1850	1910	1960	2030	2070	2140	2170	2240

Note: All Specifications are approximate. Specifications are subject to change without notice.