

Wire Rope 35Wx7



Characteristics: 3 layer of strands, rotation resistant, regular or lang lay, right hand or left hand.

钢丝绳公称直径 Nominal rope diameter (mm)	参考重量 Approx. weight (kg/100m)	钢丝绳公称抗拉强度 Rope grade (MPa)					
		1570	1670	1770	1870	1960	2160
		钢丝绳最小破断拉力 Minimum breaking load (kN)					
12	66,2	81,4	86,6	91,8	96,9	102	112
14	90,2	111	118	125	132	138	152
16	118	145	154	163	172	181	199
18	149	183	195	206	218	229	252
20	184	226	240	255	269	282	311
22	223	274	291	308	326	342	376
24	265	326	346	367	388	406	448
26	311	382	406	431	455	477	526
28	361	443	471	500	528	553	610
30	414	509	541	573	606	635	700
32	471	579	616	652	689	723	796
34	532	653	695	737	778	816	899
36	596	732	779	826	872	914	1010
38	664	816	868	920	972	1020	1120
40	736	904	962	1020	1080	1130	1240
42	811	997	1060	1120	1190	1240	1370
44	891	1090	1160	1230	1300	1370	1510
46	973	1200	1270	1350	1420	1490	1650
48	1060	1300	1390	1470	1550	1630	1790
50	1150	1410	1500	1590	1680	1760	1940
52	1240	1530	1630	1720	1820	1910	—
54	1340	1650	1750	1860	1960	2060	—
56	1440	1770	1890	2000	2110	2210	—
58	1550	1900	2020	2140	2260	2370	—
60	1660	2030	2160	2290	2420	2540	—

Note: All Specifications are approximate. Specifications are subject to change without notice.