


Wire Rope 35WxK7



| 公称直径 Nominal Diameter (mm) | 近似重量 Calculated mass (kg/100 m) | 公称抗拉强度 Norminal tesnile Strength (MPa) | | | | |
|-------------------------------------|--|--|------|------|------|------|
| | | 1570 | 1670 | 1770 | 1870 | 1960 |
| | | 钢丝绳最小破断拉力 Min. Breaking load (kN) | | | | |
| 14 | 100 | 126 | 134 | 142 | 150 | 158 |
| 16 | 131 | 165 | 175 | 186 | 196 | 206 |
| 18 | 165 | 209 | 222 | 235 | 248 | 260 |
| 20 | 204 | 257 | 274 | 290 | 307 | 321 |
| 22 | 247 | 312 | 331 | 351 | 371 | 389 |
| 24 | 294 | 371 | 394 | 418 | 442 | 463 |
| 26 | 345 | 435 | 463 | 491 | 518 | 543 |
| 28 | 400 | 505 | 537 | 569 | 601 | 630 |
| 30 | 459 | 579 | 616 | 653 | 690 | 723 |
| 32 | 522 | 659 | 701 | 743 | 785 | 823 |
| 34 | 590 | 744 | 792 | 839 | 886 | 929 |
| 36 | 661 | 834 | 887 | 941 | 994 | 1040 |
| 38 | 736 | 930 | 989 | 1050 | 1110 | 1160 |
| 40 | 816 | 1030 | 1100 | 1160 | 1230 | 1290 |
| 42 | 900 | 1140 | 1210 | 1280 | 1350 | 1420 |
| 44 | 987 | 1250 | 1330 | 1400 | 1480 | 1560 |
| 46 | 1080 | 1360 | 1450 | 1540 | 1620 | 1700 |
| 48 | 1180 | 1480 | 1580 | 1670 | 1770 | 1850 |
| 50 | 1280 | 1610 | 1710 | 1810 | 1920 | 2010 |
| 52 | 1380 | 1740 | 1850 | 1960 | 2070 | 2170 |
| 54 | 1490 | 1880 | 2000 | 2120 | 2240 | 2340 |
| 56 | 1600 | 2020 | 2150 | 2280 | 2400 | 2520 |
| 58 | 1720 | 2170 | 2300 | 2440 | 2580 | 2700 |
| 60 | 1840 | 2320 | 2460 | 2610 | 2760 | 2890 |

Note: All Specifications are approximate. Specifications are subject to change without notice.