


Wire Rope 4Vx48S+5FC



Characteristics: All strands are rotary swaged.

钢丝绳公称直径 Nominal rope diameter (mm)	参考重量 Approx. weight (kg/100m)		钢丝绳公称抗拉强度 Rope grade (MPa)				
	天然 纤维芯 NFC	合成 纤维芯 SFC	1570	1670	1770	1870	1960
			钢丝绳最小破断拉力 Minimum breaking load (kN)				
8	26.2	25.7	36.2	38.5	40.8	43.1	45.2
10	41.0	40.2	56.5	60.1	63.7	67.3	70.6
12	59.0	57.9	81.4	86.6	91.8	96.9	102
14	80.4	78.8	111	118	125	132	138
16	105	103	145	154	163	172	181
18	133	130	183	195	206	218	229
20	164	161	226	240	255	269	282
22	198	195	274	291	308	326	342
24	236	232	326	346	367	388	406
26	277	272	382	406	431	455	477
28	321	315	443	471	500	528	553
30	369	362	509	541	573	606	635
32	420	412	579	616	652	689	723
34	474	465	653	695	737	778	816
36	531	521	732	779	826	872	914
38	592	580	816	868	920	972	1020
40	656	643	904	962	1020	1080	1130

Note: All Specifications are approximate. Specifications are subject to change without notice.