


Wire Rope 4x25Fi+FC



公称直径 Nominal Diameter (mm)	近似重量 Calculated mass (kg/100 m)	公称抗拉强度 Norminal tesnile Strength (MPa)					
		1570	1670	1770	1870	1960	2160
		钢丝绳最小破断拉力 Min. Breaking load (kN)					
8	26.2	36.2	38.5	40.8	43.1	45.2	49.8
10	41.0	56.5	60.1	63.7	67.3	70.6	77.8
12	59.0	81.4	86.6	91.8	96.9	102	112
14	80.4	111	118	125	132	138	152
16	105	145	154	163	172	181	199
18	133	183	195	206	218	229	252
20	164	226	240	255	269	282	311
22	198	274	291	308	326	342	376
24	236	326	346	367	388	406	448
26	277	382	406	431	455	477	526
28	321	443	471	500	528	553	610
30	369	509	541	573	606	635	700
32	420	579	616	652	689	723	796
34	474	653	695	737	778	816	899
36	531	732	779	826	872	914	1010
38	592	816	868	920	972	1020	1120
40	656	904	962	1020	1080	1130	1240
42	723	997	1060	1120	1190	1240	1370
44	794	1090	1160	1230	1300	1370	1510
46	868	1200	1270	1350	1420	1490	1650

Note: All Specifications are approximate. Specifications are subject to change without notice.