


**Wire Rope 6Vx30+IWR**



公称直径 Nominal Diameter (mm)	近似重量 Calculated mass (kg/100 m)		公称抗拉强度 Norminal tesnile Strength (MPa)									
			1570		1670		1770		1870		1960	
			钢丝绳最小破断拉力 Min. Breaking load (kN)									
	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR
20	162	172	203	216	216	230	229	243	242	257	254	270
22	196	208	246	261	262	278	278	295	293	311	307	326
24	233	247	293	311	312	331	330	351	349	370	365	388
26	274	290	344	365	366	388	388	411	410	435	429	456
28	318	336	399	423	424	450	450	477	475	504	498	528
30	365	386	458	486	487	517	516	548	545	579	572	606
32	415	439	521	553	554	588	587	623	620	658	650	690
34	468	496	588	624	625	664	663	703	700	743	734	779
36	525	556	659	700	701	744	743	789	785	833	823	873
38	585	619	735	779	781	829	828	879	875	928	917	973

Note: All Specifications are approximate. Specifications are subject to change without notice.