


**Wire Rope 6Vx43+FC**



公称直径 Nominal Diameter (mm)	近似重量 Calculated mass (kg/100 m)		公称抗拉强度 Norminal tesnile Strength (MPa)									
			1570		1670		1770		1870		1960	
			钢丝绳最小破断拉力 Min. Breaking load (kN)									
	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR
28	318	336	443	470	471	500	500	530	528	560	553	587
30	364	386	509	540	541	574	573	609	606	643	635	674
32	415	439	579	614	616	653	652	692	689	731	723	767
34	468	485	653	693	695	737	737	782	778	826	816	866
36	525	556	732	777	779	827	826	875	872	926	914	970
38	585	619	816	856	868	921	920	976	972	1030	1020	1080
40	648	686	904	960	962	1020	1020	1080	1080	1140	1130	1200
42	714	757	997	1060	1060	1130	1120	1190	1190	1260	1240	1320
44	784	831	1090	1160	1160	1240	1230	1310	1300	1380	1370	1450
46	857	908	1200	1270	1270	1350	1350	1430	1420	1510	1490	1580
48	833	986	1300	1380	1390	1470	1470	1560	1550	1650	1630	1730
50	1010	1070	1410	1500	1500	1590	1590	1690	1680	1790	1760	1870
52	1100	1160	1530	1620	1630	1720	1720	1830	1820	1930	1910	2020
54	1180	1250	1650	1750	1750	1860	1860	1970	1960	2080	2060	2180
56	1270	1350	1770	1880	1890	2000	2000	2120	2110	2240	2210	2350
58	1360	1440	1900	2020	2020	2150	2140	2270	2280	2400	2370	2520

Note: All Specifications are approximate. Specifications are subject to change without notice.