


Wire Rope 6x12+7FC



公称直径 Nominal Diameter (mm)	近似重量 Calculated mass (kg/100 m)		公称抗拉强度 Norminal tesnile Strength (MPa)			
			1470	1570	1670	1770
	纤维芯 SC	合成芯	钢丝绳最小破断拉力 Min. Breaking load (kN)			
8	16.1	14.8	19.7	21.0	22.3	23.7
9	20.3	18.7	24.9	26.6	28.3	30.0
9.3	21.7	20.0	26.6	28.4	30.2	32.0
10	25.1	23.1	30.7	32.8	34.9	37.0
11	30.4	28.0	37.2	39.7	42.2	44.8
12	36.1	33.3	44.2	47.3	50.3	53.3
12.5	39.2	36.1	48.0	51.3	54.5	57.8
13	42.4	39.0	51.9	55.5	59.0	62.5
14	49.2	45.3	60.2	64.3	68.4	72.5
15.5	60.3	55.5	73.8	78.8	83.9	88.9
16	64.3	59.1	78.7	84.0	89.4	94.7
17	72.5	66.8	88.8	94.8	101	107
18	81.3	74.8	99.5	106	113	120
18.5	85.9	79.1	105	112	119	127
20	100	92.4	123	131	140	148
21.5	116	107	142	152	161	171
22	121	112	149	159	169	179
24	145	133	177	189	201	213
24.5	151	139	184	197	210	222
26	170	156	208	222	236	250
28	197	181	241	257	274	290
32	257	237	315	336	357	379

Note: All Specifications are approximate. Specifications are subject to change without notice.