


**Wire Rope 6x24+7FC**



公称直径 Nominal Diameter (mm)	近似重量 Calculated mass (kg/100 m)		公称抗拉强度 Norminal tesnile Strength (MPa)			
			1470	1570	1670	1770
	纤维芯 SC	合成芯	钢丝绳最小破断拉力 Min. Breaking load (kN)			
8	20.4	19.5	26.3	28.1	29.9	31.7
9	25.8	24.6	33.3	35.6	37.9	40.1
10	31.8	30.4	41.2	44.0	46.8	49.6
11	38.5	36.8	49.8	53.2	56.6	60.0
12	45.8	43.8	59.3	63.3	67.3	71.4
13	53.7	51.4	69.6	74.3	79.0	83.8
14	62.3	59.6	80.7	86.2	91.6	97.1
16	81.4	77.8	105	113	120	127
18	103	98.5	133	142	152	161
20	127	122	165	176	187	198
22	154	147	199	213	226	240
24	183	175	237	253	269	285
26	215	206	278	297	316	335
28	249	238	323	345	367	389
30	286	274	370	396	421	446
32	326	311	421	450	479	507
34	368	351	476	508	541	573
36	412	394	533	570	606	642
38	459	439	594	635	675	716
40	509	486	659	703	748	793

Note: All Specifications are approximate. Specifications are subject to change without notice.