

Wire Rope 6x24W+ 7FC



Characteristics: Parallel laid, with a large metallic cross-section, high breaking load relative to the rope diameter.

钢丝绳公称直径 Nominal rope diameter (mm)	参考重量 Approx. weight (kg/100m)		钢丝绳公称抗拉强度 Rope grade (MPa)			
	天然 纤维芯 NFC	合成 纤维芯 SFC	1470	1570	1670	1770
			钢丝绳最小破断拉力 Minimum breaking load (kN)			
			纤维芯 FC	纤维芯 FC	纤维芯 FC	纤维芯 FC
10	33.1	31.6	42.8	45.7	48.6	51.5
11	40.0	38.3	51.8	55.3	58.8	62.4
12	47.6	45.5	61.6	65.8	70.0	74.2
13	55.9	53.4	72.3	77.3	82.2	87.1
14	64.8	62.0	83.9	89.6	95.3	101
16	84.7	80.9	110	117	124	132
18	107	102	139	148	158	167
20	132	126	171	183	195	206
22	160	153	207	221	235	249
24	190	182	247	263	280	297
26	224	214	289	309	329	348
28	259	248	336	358	381	404
30	298	285	385	411	438	464
32	339	324	438	468	498	528
34	382	365	495	529	562	596
36	429	410	555	593	630	668
38	478	457	618	660	702	744
40	529	506	685	731	778	825
42	583	558	755	806	858	909
44	640	612	829	885	941	998

Note: All Specifications are approximate. Specifications are subject to change without notice.