


Wire Rope 6x55SWS+FC



| 公称直径 Nominal Diameter (mm) | 近似重量 Calculated mass (kg/100 m) | | 公称抗拉强度 Norminal tesnile Strength (MPa) | | | | | | | | | |
|-------------------------------------|--|-----------|--|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| | | | 1570 | | 1670 | | 1770 | | 1870 | | 1960 | |
| | | | 钢丝绳最小破断拉力 Min. Breaking load (kN) | | | | | | | | | |
| | 纤维芯 SC | 钢芯 IWR | 纤维芯 SC | 钢芯 IWR | 纤维芯 SC | 钢芯 IWR | 纤维芯 SC | 钢芯 IWR | 纤维芯 SC | 钢芯 IWR | 纤维芯 SC | 钢芯 IWR |
| 60 | 1390 | 1570 | 1870 | 2010 | 1980 | 2140 | 2100 | 2270 | 2220 | 2400 | 2330 | 2510 |
| 62 | 1480 | 1670 | 1990 | 2150 | 2120 | 2290 | 2250 | 2420 | 2370 | 2560 | 2490 | 2680 |
| 64 | 1580 | 1780 | 2120 | 2290 | 2260 | 2440 | 2390 | 2580 | 2530 | 2730 | 2650 | 2860 |
| 66 | 1680 | 1890 | 2260 | 2430 | 2400 | 2590 | 2540 | 2740 | 2690 | 2900 | 2820 | 3040 |
| 68 | 1780 | 2010 | 2400 | 2580 | 2550 | 2750 | 2700 | 2910 | 2850 | 3080 | 2990 | 3230 |
| 70 | 1890 | 2130 | 2540 | 2740 | 2700 | 2910 | 2860 | 3090 | 3020 | 3260 | 3170 | 3420 |
| 72 | 2000 | 2260 | 2690 | 2900 | 2860 | 3080 | 3030 | 3270 | 3200 | 3450 | 3350 | 3620 |
| 74 | 2110 | 2380 | 2840 | 3060 | 3020 | 3260 | 3200 | 3450 | 3380 | 3650 | 3540 | 3820 |
| 76 | 2230 | 2510 | 2990 | 3230 | 3180 | 3430 | 3370 | 3640 | 3560 | 3850 | 3740 | 4030 |
| 78 | 2350 | 2650 | 3150 | 3400 | 3350 | 3620 | 3550 | 3830 | 3750 | 4050 | 3940 | 4250 |
| 80 | 2470 | 2780 | 3320 | 3580 | 3530 | 3800 | 3740 | 4030 | 3950 | 4260 | 4140 | 4470 |
| 82 | 2600 | 2920 | 3480 | 3760 | 3710 | 4000 | 3930 | 4240 | 4150 | 4480 | 4350 | 4690 |
| 84 | 2720 | 3070 | 3660 | 3940 | 3890 | 4190 | 4120 | 4450 | 4350 | 4700 | 4560 | 4920 |
| 86 | 2850 | 3220 | 3830 | 4130 | 4080 | 4400 | 4320 | 4660 | 4560 | 4920 | 4780 | 5160 |

Note: All Specifications are approximate. Specifications are subject to change without notice.