


Wire Rope 6x61+IWR



公称直径 Nominal Diameter (mm)	近似重量 Calculated mass (kg/100 m)		公称抗拉强度 Norminal tesnile Strength (MPa)									
			1570		1670		1770		1870		1960	
			钢丝绳最小破断拉力 Min. Breaking load (kN)									
	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR
60	1300	1430	1600	1730	1730	1840	1800	1950	1910	2060	2000	2160
62	1390	1530	1710	1850	1850	1960	1930	2080	2030	2200	2130	2310
64	1480	1630	1820	1970	1970	2090	2050	2220	2170	2340	2270	2460
66	1570	1730	1940	2090	2090	2230	2180	2360	2310	2490	2420	2610
68	1670	1840	2050	2220	2220	2360	2320	2500	2450	2650	2560	2770
70	1770	1950	2180	2350	2350	2500	2450	2650	2590	2800	2720	2940
72	1870	2060	2300	2490	2490	2650	2600	2810	2740	2970	2880	3110
74	1980	2180	2430	2630	2630	2800	2740	2970	2900	3130	3040	3280
76	2090	2300	2570	2770	2770	2950	2890	3130	3060	3310	3200	3460
78	2200	2120	2700	2920	2920	3110	3050	3300	3220	3480	3370	3650
80	2310	2550	2840	3070	3070	3270	3210	3470	3390	3660	3550	3840
82	2430	2680	2990	3230	3230	3440	3370	3640	3560	3850	3730	4030
84	2550	2810	3140	3390	3390	3610	3530	3820	3730	4040	3910	4230
86	2670	2940	3290	3550	3550	3780	3700	4010	3910	4230	4100	4440
88	2800	3080	3440	3720	3720	3960	3880	4190	4100	4430	4300	4640
90	2920	3220	3600	3890	3890	4140	4060	4390	4290	4630	4490	4860

Note: All Specifications are approximate. Specifications are subject to change without notice.