


**Wire Rope 6x61FWS+IWR**



公称直径 Nominal Diameter (mm)	近似重量 Calculated mass (kg/100 m)		公称抗拉强度 Norminal tesnile Strength (MPa)									
			1570		1670		1770		1870		1960	
			钢丝绳最小破断拉力 Min. Breaking load (kN)									
	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR
60	1390	1570	1870	2010	1980	2140	2100	2270	2220	2400	2330	2510
62	1480	1670	1990	2150	2120	2290	2250	2420	2370	2560	2490	2680
64	1580	1780	2120	2290	2260	2440	2390	2580	2530	2730	2650	2860
66	1680	1890	2260	2430	2400	2590	2540	2740	2690	2900	2820	3040
68	1780	2010	2400	2580	2550	2750	2700	2910	2850	3080	2990	3230
70	1890	2130	2540	2740	2700	2910	2860	3090	3020	3260	3170	3420
72	2000	2260	2690	2900	2860	3080	3030	3270	3200	3450	3350	3620
74	2110	2380	2840	3060	3020	3260	3200	3450	3380	3650	3540	3820
76	2230	2510	2990	3230	3180	3430	3370	3640	3560	3850	3740	4030
78	2350	2650	3150	3400	3350	3620	3550	3830	3750	4050	3940	4250
80	2470	2780	3320	3580	3530	3800	3740	4030	3950	4260	4140	4470
82	2600	2920	3480	3760	3710	4000	3930	4240	4150	4480	4350	4690
84	2720	3070	3660	3940	3890	4190	4120	4450	4350	4700	4560	4920
86	2850	3220	3830	4130	4080	4400	4320	4660	4560	4920	4780	5160

Note: All Specifications are approximate. Specifications are subject to change without notice.