


Wire Rope 6xK31WS+IWR



公称直径 Nominal Diameter (mm)	近似重量 Calculated mass (kg/100 m)		公称抗拉强度 Norminal tesnile Strength (MPa)							
			1570		1670		1770		1870	
			钢丝绳最小破断拉力 Min. Breaking load (kN)							
	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR
12	61.2	68.7	84.3	92.7	89.7	98.6	95.1	105	100	110
14	83.3	93.5	115	126	122	134	129	142	137	150
16	109	122	150	165	159	175	169	186	179	196
18	138	154	190	209	202	222	214	235	226	248
20	170	190	234	257	249	274	264	290	279	307
22	206	230	283	312	301	331	320	351	338	371
24	245	274	337	371	359	394	380	418	402	442
26	287	321	396	435	421	463	446	491	472	518
28	333	372	459	505	488	537	518	569	547	601
30	382	428	527	579	561	616	594	653	628	690
32	435	486	600	659	638	701	676	743	714	785
34	491	549	677	744	720	792	763	839	806	886
36	551	616	759	834	807	887	856	941	904	994
38	614	686	846	930	899	989	953	1050	1010	1110
40	680	760	937	1030	997	1100	1060	1160	1120	1230
42	750	838	1030	1140	1100	1210	1160	1280	1230	1350
44	823	920	1130	1250	1210	1330	1280	1400	1350	1480
46	899	1010	1240	1360	1320	1450	1400	1541	1480	1620
48	979	1090	1350	1480	1440	1580	1520	1670	1610	1770
50	1060	1190	1460	1610	1560	1710	1650	1810	1740	1920
52	1150	1280	1580	1740	1680	1850	1790	1960	1890	2070
54	1240	1390	1710	1880	1820	2000	1930	2120	2030	2240
56	1330	1490	1840	2020	1950	2150	2070	2280	2190	2400
58	1430	1600	1970	2170	2100	2300	2220	2440	2350	2580
60	1530	1720	2110	2320	2240	2460	2380	2610	2510	2760
62	1630	1830	2250	2470	2390	2630	2540	2790	2680	2950
64	1740	1950	2400	2640	2550	2800	2700	2970	2860	3140
66	1850	2080	2550	2800	2710	2980	2880	3160	3040	3340
68	1970	2210	2710	2980	2880	3170	3050	3360	3030	3550

Note: All Specifications are approximate. Specifications are subject to change without notice.