


**Wire Rope 8x49SWS+IWR**



公称直径 Nominal Diameter (mm)	近似重量 Calculated mass (kg/100 m)		公称抗拉强度 Norminal tesnile Strength (MPa)									
			1570		1670		1770		1870		1960	
			钢丝绳最小破断拉力 Min. Breaking load (kN)									
	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR
60	1350	1600	1660	1960	1760	2080	1870	2200	1970	2330	2070	2440
62	1440	1710	1770	2090	1880	2220	1990	2350	2110	2490	2210	2610
64	1540	1820	2990	2230	2000	2370	2120	2510	2240	2650	2350	2780
66	1630	1940	2000	2370	2130	2520	2260	2670	2390	2820	2500	2950
68	1730	2060	2130	2510	2260	2670	2400	2830	2530	2990	2660	3140
70	1840	2180	2250	2660	2400	2830	2540	3000	2680	3170	2810	3320
72	1940	2310	2380	2820	2540	3000	2690	3170	2840	3350	2960	3520
74	2050	2440	2520	2970	2680	3160	2840	3350	3000	3540	3140	3710
76	2170	2570	2660	3140	2830	3340	3000	3540	3160	3740	3320	3920
78	2280	2710	2800	3300	2980	3520	3160	3730	3330	3940	3490	4130
80	2400	2850	2940	3480	3130	3700	3320	3920	3510	4140	3680	4340
82	2520	2990	3090	3650	3290	3890	3490	4120	3680	4250	3860	4560
84	2650	3140	3250	3830	3450	4080	3660	4320	3870	4570	4050	4790
86	2770	3290	3400	4020	3620	4270	3840	4530	4050	4790	4250	5020
88	2900	3450	3560	4210	3790	4470	4020	4740	4240	5010	4450	5250
90	3040	3600	3730	4400	3960	4680	4200	4960	4440	5240	4650	5490
92	3170	3770	3890	4600	4140	4890	4390	5180	4640	5480	4860	5740
94	3310	3930	4060	4800	4320	5440	4580	5410	4840	5720	5070	5990
96	3460	4100	4240	5010	4510	5330	4780	5640	5050	5960	5290	6250
98	3600	4270	4420	5220	4700	5550	4980	5880	5260	6210	5520	6510
100	3750	4450	4600	5430	4890	5780	5190	6120	5480	6470	5740	6780

Note: All Specifications are approximate. Specifications are subject to change without notice.