


**Wire Rope 8x61+IWR**



公称直径 Nominal Diameter (mm)	近似重量 Calculated mass (kg/100 m)		公称抗拉强度 Norminal tesnile Strength (MPa)									
			1570		1670		1770		1870		1960	
			钢丝绳最小破断拉力 Min. Breaking load (kN)									
	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR
60	1280	1490	1420	1680	1510	1790	1600	1890	1690	2000	1770	2100
62	1370	1600	1510	1790	1610	1910	1710	2020	1800	2130	1890	2240
64	1460	1700	1610	1910	1720	2030	1820	2150	1920	2270	2020	2380
66	1550	1810	1720	2030	1830	2160	1940	2290	2040	2420	2140	2540
68	1650	1920	1820	2160	1940	2290	2050	2430	2170	2570	2270	2600
70	1740	2030	1930	2280	2050	2430	2180	2580	2300	2720	2410	2850
72	1820	2150	2040	2420	2170	2570	2300	2730	2430	2880	2550	3020
74	1950	2270	2160	2550	2300	2720	2430	2880	2570	3040	2690	3190
76	2060	2400	2280	2690	2420	2860	2570	3040	2710	3210	2840	3360
78	2170	2520	2400	2840	2550	3020	2700	3200	2860	3380	2990	3540
80	2280	2660	2520	2980	2680	3170	2840	3360	3000	3550	3150	3730
82	2390	2790	2650	3140	2820	3340	2990	3530	3160	3730	3310	3910
84	2510	2930	2780	3290	2960	3500	3130	3710	3310	3920	3470	4110
86	2630	3070	2910	3450	3100	3670	3290	3890	3470	4110	3640	4310
88	2760	3210	3050	3640	3250	3840	3440	4070	3630	4300	3810	4510
90	2880	3360	3190	3780	3400	4020	3600	4260	3800	4500	3980	4720
92	3010	3510	3340	3950	3550	4200	3760	4450	3970	4700	4160	4930
94	3150	3670	3480	4120	3700	4380	3930	4640	4150	4910	4350	5140
96	3280	3820	3630	4300	3860	4570	4090	4840	4330	5120	4530	5360
98	3420	3990	3780	4480	4030	4760	4270	5050	4510	5330	4720	5590
100	3560	4150	3940	4660	4190	4960	4440	5260	4690	5550	4920	5820

Note: All Specifications are approximate. Specifications are subject to change without notice.