


**Wire Rope 8xK36WS+IWR**



公称直径 Nominal Diameter (mm)	近似重量 Calculated mass (kg/100 m)		公称抗拉强度 Norminal tesnile Strength (MPa)							
			1570		1670		1770		1870	
			钢丝绳最小破断拉力 Min. Breaking load (kN)							
	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR
16	104	127	133	165	140	175	150	186	158	196
18	131	160	168	209	179	222	189	235	200	248
20	162	198	207	257	220	274	234	290	247	307
22	196	240	256	312	272	331	283	351	305	371
24	233	282	305	371	324	394	344	418	363	442
26	274	331	358	435	380	463	403	491	426	518
28	318	384	415	505	441	537	468	569	494	601
30	364	441	476	579	507	616	537	653	567	690
32	415	502	542	659	576	701	611	743	645	785
34	468	566	612	744	651	792	690	839	728	886
36	525	635	686	834	729	887	773	941	817	994
38	585	708	764	930	813	989	861	1050	910	1110
40	648	784	847	1030	900	1100	954	1160	1010	1230
42	714	864	933	1140	993	1210	1050	1280	1110	1350
44	784	949	1020	1250	1090	1330	1150	1400	1220	1480
46	857	1040	1120	1360	1190	1450	1260	1540	1330	1620
48	933	1130	1220	1480	1300	1580	1370	1670	1450	1770
50	1010	1220	1320	1610	1410	1710	1490	1810	1580	1920
52	1100	1320	1430	1740	1520	1820	1610	1960	1700	2070
54	1180	1430	1540	1880	1640	2000	1740	2120	1840	2240
56	1270	1540	1660	2020	1760	2150	1870	2280	1980	2400
58	1360	1650	1780	2170	1890	2300	2010	2440	2120	2580
60	1460	1760	1900	2320	2030	2460	2150	2610	2270	2760
62	1560	1900	1990	2470	2120	2630	2250	2790	2370	2950
64	1660	2030	2120	2640	2260	2800	2390	2970	2530	3140
66	1760	2160	2260	2800	2400	2980	2540	3160	2690	3340
68	1870	2290	2400	2980	2550	3170	2700	3360	2850	3550
70	1980	2430	2540	3150	2700	3360	2860	3560	3020	3760

Note: All Specifications are approximate. Specifications are subject to change without notice.