


Wire Rope DL1212HK



Characteristics: Outer strands are compacted, with high breaking strength and good resistance to drum crushing.

钢丝绳公称直径 Nominal rope diameter		参考重量 Approx. weight (kg/100m)	钢丝绳公称抗拉强度 Rope grade (MPa)				参考重量 Approx. weight (kg/100m)	钢丝绳公称抗拉强度 Rope grade (MPa)			
d	允许偏差 Tolerance (%)		1670	1770	1870	1960		1670	1770	1870	1960
(mm)			钢丝绳最小破断拉力 Minimum breaking load (kN)					钢丝绳最小破断拉力 Minimum breaking load (kN)			
12	+ 4 - 1	67.0	93.8	99.4	105	110	67.7	98.6	105	110	116
13		78.6	110	117	123	129	79.4	116	123	130	136
14		91.1	128	135	143	150	92.1	134	142	150	158
15		105	147	155	164	172	106	154	163	173	181
16		119	167	177	187	196	120	175	186	196	206
17		134	188	199	211	221	136	198	210	222	232
18		151	211	224	236	248	152	222	235	248	260
19		168	235	249	263	276	170	247	262	277	290
20		186	261	276	292	306	188	274	290	307	321
21		205	287	304	322	337	207	302	320	338	354
22		225	315	334	353	370	227	331	351	371	389
23		246	345	365	386	404	249	362	384	406	425
24		268	375	398	420	440	271	394	418	442	463
25		291	407	431	456	478	294	428	454	479	502
26		314	440	467	493	517	318	463	491	518	543
27		339	475	503	532	557	343	499	529	559	586
28		365	511	541	572	599	368	537	569	601	630
29		391	548	581	613	643	395	576	610	645	676
30		419	586	621	656	688	423	616	653	690	723
32		476	(667)	(707)	(747)	(783)	481	(701)	(743)	(785)	(823)
34		538	(753)	(798)	(843)	(884)	543	(792)	(839)	(886)	(929)
36		603	(844)	(895)	(945)	(991)	609	(887)	(941)	(994)	(1041)
38		671	(940)	(997)	(1053)	(1104)	679	(989)	(1048)	(1107)	(1160)
40		744	(1042)	(1104)	(1167)	(1223)	752	(1096)	(1161)	(1227)	(1286)

Data in () is not for DL1212HK or DL1212AK.

Note: All Specifications are approximate. Specifications are subject to change without notice.