


Wire Rope DL1916HK



Characteristics: Outer strands are compacted, with high breaking strength and good resistance to drum crushing.

| 钢丝绳公称直径 Nominal rope diameter | | 参考重量 Approx. weight (kg/100m) | 钢丝绳公称抗拉强度 Rope grade (MPa) | | | | 参考重量 Approx. weight (kg/100m) | 钢丝绳公称抗拉强度 Rope grade (MPa) | | | |
|----------------------------------|-------------------|-------------------------------------|--------------------------------------|----------|----------|----------|-------------------------------------|--------------------------------------|----------|----------|----------|
| d | 允许偏差 Tolerance | | 1670 | 1770 | 1870 | 1960 | | 1670 | 1770 | 1870 | 1960 |
| (mm) | (%) | | 钢丝绳最小破断拉力 Minimum breaking load (kN) | | | | | 钢丝绳最小破断拉力 Minimum breaking load (kN) | | | |
| 12 | + 4 - 1 | 67.0 | 93.8 | 99.4 | 105 | 110 | 67.7 | 98.6 | 105 | 110 | 116 |
| 13 | | 78.6 | 110 | 117 | 123 | 129 | 79.4 | 116 | 123 | 130 | 136 |
| 14 | | 91.1 | 128 | 135 | 143 | 150 | 92.1 | 134 | 142 | 150 | 158 |
| 15 | | 105 | 147 | 155 | 164 | 172 | 106 | 154 | 163 | 173 | 181 |
| 16 | | 119 | 167 | 177 | 187 | 196 | 120 | 175 | 186 | 196 | 206 |
| 17 | | 134 | 188 | 199 | 211 | 221 | 136 | 198 | 210 | 222 | 232 |
| 18 | | 151 | 211 | 224 | 236 | 248 | 152 | 222 | 235 | 248 | 260 |
| 19 | | 168 | 235 | 249 | 263 | 276 | 170 | 247 | 262 | 277 | 290 |
| 20 | | 186 | 261 | 276 | 292 | 306 | 188 | 274 | 290 | 307 | 321 |
| 21 | | 205 | 287 | 304 | 322 | 337 | 207 | 302 | 320 | 338 | 354 |
| 22 | | 225 | 315 | 334 | 353 | 370 | 227 | 331 | 351 | 371 | 389 |
| 23 | | 246 | 345 | 365 | 386 | 404 | 249 | 362 | 384 | 406 | 425 |
| 24 | | 268 | 375 | 398 | 420 | 440 | 271 | 394 | 418 | 442 | 463 |
| 25 | | 291 | 407 | 431 | 456 | 478 | 294 | 428 | 454 | 479 | 502 |
| 26 | | 314 | 440 | 467 | 493 | 517 | 318 | 463 | 491 | 518 | 543 |
| 27 | | 339 | 475 | 503 | 532 | 557 | 343 | 499 | 529 | 559 | 586 |
| 28 | | 365 | 511 | 541 | 572 | 599 | 368 | 537 | 569 | 601 | 630 |
| 29 | | 391 | 548 | 581 | 613 | 643 | 395 | 576 | 610 | 645 | 676 |
| 30 | | 419 | 586 | 621 | 656 | 688 | 423 | 616 | 653 | 690 | 723 |
| 32 | | 476 | (667) | (707) | (747) | (783) | 481 | (701) | (743) | (785) | (823) |
| 34 | | 538 | (753) | (798) | (843) | (884) | 543 | (792) | (839) | (886) | (929) |
| 36 | | 603 | (844) | (895) | (945) | (991) | 609 | (887) | (941) | (994) | (1041) |
| 38 | | 671 | (940) | (997) | (1053) | (1104) | 679 | (989) | (1048) | (1107) | (1160) |
| 40 | | 744 | (1042) | (1104) | (1167) | (1223) | 752 | (1096) | (1161) | (1227) | (1286) |

Note: All Specifications are approximate. Specifications are subject to change without notice.