

New Generator Series

MBG1200 MBG3500 MBG5500(E) MBG6500(E)

- AVR ensures stable output and operation in extreme environment.
- Large fuel tank design provides extended operating times.
- Power output increase of 20%.

Luxury Generator Series

MBG1802 MBG2902

- Aluminum alloy frame design provides light weight and compact size.
- Weather resistant front panel protects internal components.
- Ergonomically designed features leading to unparalleled portability and stability.



Model Number	MBG1200	MBG1802	MBG2902	MBG3500	MBG5500(E)	MBG6500(E)
Alternator	Self-exciting single phase two pole					
Туре	Brush					
Voltage regulation	AVR					
Frequency (Hz)	50	50	50	50	50	50
Max. output (KW)	1.0	1.8	2.8	2.8	4.2	5.5
Rated output (KW)	0.85	1.5	2.5	2.5	3.8	5.0
Voltage (V)	220, 230, 240					
Power factor	1.0					
Engine						
Model number	GT241	GT400	GT600	GT600	GT1000	GT1300
Туре	Air cooled 4-stroke OHV single cylinder gasoline engine					
Displacement (cc)	79.6	126	181	181	296	391
Fuel type	Unleaded	Unleaded	Unleaded	Unleaded	Unleaded	Unleaded
	Gasoline	Gasoline	Gasoline	Gasoline	Gasoline	Gasoline
Lube grade	SE or higher	SE or higher	SE or higher	SE or higher	SE or higher	SE or higher
Lube capacity (L)	0.4	0.6	0.6	0.6	1.2	1.2
Ignition system	Breakerless Ignition Type					
Starting system	Recoil	Recoil	Recoil	Recoil	Recoil/Electric	Recoil/Electric
Packing and weight		70		20	5X	
Unit dimension (mm)	470x380x390	610x440x515	610x440x515	575x440x480	755x505x570	755x505x570
Packing dimension (mm)	490x410x430	635x475x535	635x475x535	600x475x510	780x530x600	780x530x600
Net weight (Kg)	27.5	43	48	45	79	85
Standard equipments		- 16 · · · · · · · · · · · · · · · · · ·		10	***	
Low oil shut down	•	•	•	•	•	•
Oil alarm lamp	•	•	•	•	•	•
Fuel gauge	•	•	•	•	•	•
AC breaker		•	•	•	•	•
Voltmeter	•	•	•	•	•	•
Hour meter	•	•	•	•	•	•
Portability Kit		•	•		•	•