



Skid Steer Loader  
» **JC75**



进口液压件  
Hydraulic system from abroad

道依茨、珀金斯、康明斯发动机 易于维护Rops/Fops驾驶室设计  
Deutz, perkins Cummins brand diesel engine Rops/Fops CAB IN WITH EASY MAINTENANCE DESIGN

快换装置  
Standard quick hitch

**Main features of JC75**

- Compact structure, maneuverable movement suitable for narrow space operation
- Close cabin with joystick control system
- Extended wheelbase
- High flow double output
- Double accelerograph control
- Auto-leveling system
- Multi-function with a wide range of attachments
- Hydraulic brake

**Specifications**

额定载重	Rated Operating Capacity	1050
倾翻载荷	Tipping load(Kg)	2100
铲斗容量	Bucket Capacity(m <sup>3</sup> )	0.55
提升力	Lifting Force(Kg)	2400
工作流量	Hydraulic Pump Flow(L/min)	75/125
功率	Engine power(HP)	75
机重	Weight(Kg)	3500
速度	Max.Travel Speed (km/h)	12/18
最大爬坡	Grade ability(°)	20
轮胎规格	Tire	12-16.5
燃油、液压油容量	Fuel/hyd.oil capacity(L)	90/90

**Dimensions**

最大操作高度	A.Height at Maximum Extension	4070mm
铰接销高度	B.Hinge Pin Height	3150mm
总高度	C.Total Height	2050mm
带斗总长度	D.Length with Bucket	3560mm
无斗长度	E.Length without Bucket	2780mm
带斗宽度	F.Width with Bucket	1900mm
轮距	G.Track Width	1500mm
轴距	H.Wheelbase	1185mm
离地高度	J.Ground Clearance	200mm
倾倒角	K.Dumping Angle	40°
倾倒高度	L.Dumping Height	2450mm
倾倒前伸	M.Maximum Reach	710mm

**Dimensional Drawings**

