



Skid Steer Loader
» **TS100**



长轴距履带
Long Wheelbase Rubber Track



德国、日本液压元件
German & Japanese hydraulic parts



易于维护保养 ROPS/FOPS 驾驶室
Easy maintenance Design with ROPS/FOPS Cabin



快换装置
Standard quick hitch

Main features of TS100

- Compact structure, maneuverable movement suitable for narrow space operation
- Close cabin with joystick control system
- Double accelerograph control
- Auto-leveling system
- Multi-function with a wide range of attachments
- Hydraulic brake

Specifications

额定载重	Rated Operating Capacity	1500
倾翻载荷	Tipping load(Kg)	3000
铲斗容量	Bucket Capacity(m³)	0.6-0.7
提升力	Lifting Force(Kg)	2200
工作流量	Hydraulic Pump Flow(L/min)	100/150
功率	Engine power(HP)	100
机重	Weight(Kg)	4280
速度	Max.Travel Speed km/h	8/16
最大爬坡	Grade ability (°)	20
燃油、液压油容量	Fuel/hyd.oil capacity(L)	85

Dimensions

总高度	A-Height to top of ROPS	2110mm
离地高度	B-Ground clearance	205mm
最大提升高度	C-Max.lift height, at hinge pin	2920mm
履带底盘长度	E-Length of undercarriage	1938mm
去铲斗长度	F-Machine length without bucket	2676mm
带斗长度	G-Machine length with bucket	3385mm
总宽度	H-Machine width:	1850mm
履带宽度	I-Track width:	320mm
履带地面长度	D-Length of track on ground:	1500mm

Dimensional Drawings

