

Specifications

Articulated Boom Lifts

and were the control of the control	GTQZ16
最大工作高度	17.3
Max. working height (m)	17.5
最大平台高度	15.25
Max. platform height (m)	
工作幅度	9.1
Horizontal reach (m)	WARRING TO THE PARTY OF THE PAR
最大作业高度时的幅度(距回转中心)	3.6
Max. up and over clearance (m)	
观格尺寸 Dimensions (mm)	
	7550
(A) 总长Overall length	7550
(B)总宽Overall width	2170
(C) 总高Overall height	2120
(D) 平台长Platform length	1800
(E)平台宽Platform width	760
(F)平台高Platform height	1170
(G) 轴距Axle base	2200
(H) 底车离地间隙Ground clearance	400
顔定载荷 ifting capacity (kg)	230
edeleting capacity (Ng) edele	255 (non continuously)
Furntable rotation (°)	355 (non-continously)
工作平台回转	180
Platform rotation (°)	160
些 坡能力(臂架全缩)	45
Gradeability (Boom fully retracted) (%)	·-
最大行驶速度	
Max. traveling speed (km/h)	
臂架全缩	6
Boom fully retracted	
臂架全伸 Boom fully extended	1
发动机功率	
文列化切 学 Ingine power (kW)	37.3
系统电压	
/oltage (V)	12
然油箱容积	10
ruel tank capacity (L)	40
夜压箱容积	00
lydraulic tank capacity (L)	90
整机质量	7800
Machine weight (kg)	, 000