





技术参数	TECHNICAL DATA	单位 UNITS	参数值 PARAMETER VALUE
额定斗容量	Rated capacity for bucket	m ³	1
额定装载质量	Rated loading	kg	1800
掘起力	Break out force	kN	45
最大牵引力	Maximum tractive effort	kN	38
倾翻载荷	Tipping load	kN	30
车速	Travel speed	km/h	
前进一档	Travel speed in forward 1 st	km/h	0-11
前进二档	Travel speed in forward 2 nd	km/h	0-27
后退一档	Travel speed in reverse 1 st	km/h	0-11
后退二档	Travel speed in reverse 2 nd	km/h	0-27
卸载高度(加长臂)H	Dump height	mm	2600 (2900)
最大卸载高度时的卸载距离	Reach fully raised	mm	930
卸载角	Dump angle	°	45
运输位置时的铲斗最大收斗角	Reach fully raised	°	50
铲斗提升时间	Raising time for bucket	S	5.2
铲斗下降时间	Lowering time for bucket	S	3.4
发动机型号	Engine model		4102BG或4102GB
标定功率	Engine rated power	kw	50
标定转速	Engine rated revolutions per minute	r/min	2400
最大转向角(a)	Maximum articulation angle	°	左右35
最大爬坡能力	Maximum climbing capacity	%	60
最小转弯半径(R)(铲斗外侧)	Minimum turning radius, with bucket in carry position	mm	4700
整机操作质量	Operating mass	kg	5700(5800)
外型尺寸(长X宽X高)	Overall dimension(L x W x H)	mm	5216 x 1950 x 2715 (5390 x 1950 x 2715)

敬告：请选用我公司和我公司指定配件经销点的正宗配件。



若技术变化，不另行通知 The technical data may be changed without notice