



Model		XT670-140		XT680-170	
Description	Unit	Specifications		Specifications	
Overall dimensions(L*W*H)	mm	6290×2450×2725		6890×2500×2815	
Working weight	kg	10500		13600	
min.ground clearance	mm	450		400	
Wheel base	mm	3250		3900	
Tread	mm	1977		2060	
Engine		PERKINS/1104D-44T/ Duzts TD226B-4IG2		CUMMINUS QSB4.5	
Rated power	kw	74.5		82	
Rated speed	r/min	2200		2200	
displacement	L	4.4		4.4	
No.of cylinder		4		4	
Max. speed	km/h	35		37	
Fork length	mm	1200		1200	
Rear	mm	1190		1055	
Departure angle	°	36.4		46	
Min.turning radius	mm	4238		4860	
Max. climbing capacity	°	26.5		33.2	
foot brake/brake oil pressure	Mpa	wet type/4.4		wet type/4.4	
hand brake		wet type/4.4		wet type/4.4	
Specs		outriggers on ground	outriggers are not ground	outriggers on ground	outriggers are not ground
Maximum lift capacity	Kg	3500	3500	4500	4500
Lift capacity to full height	Kg	2269	1350	2269	1361
Lift capacity at full reach	kg	453	225	453	0
Lift height	mm	13800	13500	16700	13060
Reach at maximum lift height	mm	1330	1955	1063	2130
Maximum forward reach	mm	8830	9457	12600	9140

NOTICE: All dimensions are approximate. Specifications are subject to change without notice.