


Wire Rope 1x19



公称直径 Nominal Diameter (mm)	近似重量 Calculated mass (kg/100 m)	公称抗拉强度 Norminal tesnile Strength (MPa)			
		1570	1670	1770	1870
		钢丝绳最小破断拉力 Min. Breaking load (kN)			
1	0.51	0.83	0.89	0.94	0.99
1.5	1.14	1.87	1.99	2.11	2.23
2	2.03	3.33	3.54	3.75	3.96
2.5	3.17	5.20	5.53	5.86	6.19
3	4.56	7.49	7.97	8.44	8.92
3.5	6.21	10.2	10.8	11.5	12.1
4	8.11	13.3	14.2	15.0	15.9
4.5	10.3	16.9	17.9	19.0	20.1
5	12.7	20.8	22.1	23.5	24.8
5.5	15.3	25.2	26.8	28.4	30.0
6	18.3	30.0	31.9	33.8	35.7
6.5	21.4	35.2	37.4	39.6	41.9
7	24.8	40.8	43.4	46.0	48.6
7.5	28.5	46.8	49.8	52.8	55.7
8	32.4	56.6	56.6	60.0	63.4
8.5	36.6	60.1	63.9	67.8	71.6
9	41.1	67.4	71.7	76.0	80.3
10	50.7	83.2	88.6	93.8	99.1
11	61.3	101	107	114	120
12	73.0	120	127	135	143
13	85.7	141	150	159	167
14	99.4	163	173	184	194
15	114	187	199	211	223
16	130	213	227	240	254

Note: All Specifications are approximate. Specifications are subject to change without notice.