


Wire Rope 6Vx37S+IWR



公称直径 Nominal Diameter (mm)	近似重量 Calculated mass (kg/100 m)		公称抗拉强度 Norminal tesnile Strength (MPa)									
			1570		1670		1770		1870		1960	
			钢丝绳最小破断拉力 Min. Breaking load (kN)									
	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR
32	427	452	596	633	634	673	672	713	710	753	744	790
34	482	511	673	714	715	760	759	805	802	851	840	891
36	541	573	754	801	803	852	851	903	899	954	942	999
38	602	638	841	892	894	949	948	1010	1000	1060	1050	1110
40	667	707	931	988	991	1050	1050	1110	1110	1180	1160	1230
42	738	779	1030	1090	1090	1160	1160	1230	1220	1300	1280	1360
44	808	855	1130	1200	1200	1270	1270	1350	1340	1420	1410	1490
46	883	935	1230	1310	1310	1390	1390	1470	1470	1560	1540	1630
48	961	1020	1340	1420	1430	1510	1510	1600	1600	1700	1670	1780
50	1040	1100	1460	1540	1550	1640	1640	1740	1730	1840	1820	1930
52	1130	1190	1570	1670	1670	1780	1770	1880	1870	1990	1970	2090

Note: All Specifications are approximate. Specifications are subject to change without notice.