

Wire Rope 6x80WSNS+IWR



公称直径 Nominal Diameter (mm)	近似重量 Calculated mass (kg/100 m)		公称抗拉强度 Norminal tesnile Strength (MPa)									
			1570		1670		1770		1870		1960	
			钢丝绳最小破断拉力 Min. Breaking load (kN)									
	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR
60	1370	1570	1800	1960	1910	2080	2030	2200	2140	2330	2240	2440
62	1460	1670	1920	2090	2040	2220	2160	2350	2290	2490	2400	2610
64	1560	1780	2040	2230	2180	2370	2310	2510	2440	2650	2550	2780
66	1660	1890	2170	2370	2310	2520	2450	2670	2590	2820	2720	2950
68	1760	2010	2310	2510	2450	2670	2600	2830	2750	2990	2880	3140
70	1860	2130	2450	2660	2600	2830	2760	3000	2910	3170	3050	3320
72	1970	2260	2590	2820	2750	3000	2920	3170	3080	3350	3230	3520
74	2080	2380	2730	2970	2910	3160	3080	3350	3260	3540	3410	3710
76	2190	2510	2880	3140	3070	3340	3250	3540	3430	3740	3600	3920
78	2310	2650	3040	3300	3230	3520	3420	3730	3620	3940	3790	4130
80	2430	2780	3200	3480	3400	3700	3600	3920	3810	4140	3990	4340
82	2560	2920	3360	3650	3570	3890	3780	4120	4000	4350	4190	4560
84	2680	3070	3520	3830	3750	4080	3970	4320	4200	4570	4400	4790
86	2810	3220	3690	4020	3930	4270	4160	4530	4400	4790	4610	5020
88	2940	3370	3870	4210	4110	4470	4470	4740	4610	5010	4830	5250
90	3080	3520	4040	4400	4300	4680	4680	4960	4820	5240	5050	5490

Note: All Specifications are approximate. Specifications are subject to change without notice.