


Wire Rope 8x84WSNS+IWR



公称直径 Nominal Diameter (mm)	近似重量 Calculated mass (kg/100 m)		公称抗拉强度 Norminal tesnile Strength (MPa)									
			1570		1670		1770		1870		1960	
			钢丝绳最小破断拉力 Min. Breaking load (kN)									
	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR	纤维芯 SC	钢芯 IWR
60	1330	1590	1530	1900	1620	2020	1720	2140	1820	2260	1910	2370
62	1420	1700	1630	2030	1730	2160	1840	2290	1940	2420	2030	2530
64	1520	1810	1740	2160	1850	2300	1960	2440	2070	2570	2170	2700
66	1610	1930	1850	2300	1960	2440	2080	2950	2200	2740	2310	2870
68	1710	2050	1960	2440	2080	2590	2210	2750	2330	2910	2450	3050
70	1810	2170	2080	2580	2210	2750	2340	2910	2470	3080	2590	3230
72	1920	2300	2200	2730	2340	2910	2480	3080	2620	3260	2740	3410
74	2030	2430	2320	2890	2470	3070	2620	3260	2760	3440	2900	3610
76	2140	2560	2450	3050	2600	3240	2760	3440	2920	3630	3060	3800
78	2250	2700	2580	3210	2740	3410	2910	3620	3070	3820	3220	4010
80	2370	2840	2710	3380	2890	3590	3060	3810	3230	4020	3390	4210
82	2490	2980	2850	3550	3030	3770	3210	4000	3390	4220	3560	4430
84	2610	3130	2990	3720	3180	3960	3370	4200	3560	4430	3730	4650
86	2740	3280	3140	3900	3330	4150	3530	4400	3730	4650	3910	4870
88	2870	3430	3280	4090	3490	4350	3700	4610	3910	4870	4100	5100
90	3000	3590	3430	4270	3650	4550	3870	4820	4090	5090	4290	5330
92	3130	3750	3590	4460	3820	4750	4040	5030	4270	5320	4480	5570
94	3270	3910	3750	4660	3980	4960	4220	5250	4460	5550	4680	5820
96	3410	4080	3910	4860	4160	5170	4400	5480	4650	5790	4880	6070
98	3550	4250	4070	5070	4330	5390	4590	5710	4850	6030	5080	6320
100	3700	4430	4240	5280	4510	5610	4780	5950	5050	6280	5290	6590

Note: All Specifications are approximate. Specifications are subject to change without notice.