


Wire Rope DL1315HK



Characteristics: Rotation resistant, outer strands are compact strands.

钢丝绳公称直径 Nominal rope diameter		参考重量 Approx. weight (kg/100m)	钢丝绳公称抗拉强度 Rope grade (MPa)				参考重量 Approx. weight (kg/100m)	钢丝绳公称抗拉强度 Rope grade (MPa)			
d	允许偏差 Tolerance (%)		1670	1770	1870	1960		1670	1770	1870	1960
(mm)			钢丝绳最小破断拉力 Minimum breaking load (kN)					钢丝绳最小破断拉力 Minimum breaking load (kN)			
12	+4 -1	69.1	106	112	118	124	71.3	111	117	124	130
13		81.1	124	132	139	146	83.7	130	138	145	152
14		94.1	144	153	161	169	97.0	151	160	169	177
15		108	165	175	185	194	111	173	183	194	203
16		123	188	199	211	221	127	197	208	220	231
17		139	212	225	238	249	143	222	235	249	261
18		156	238	252	267	279	160	249	264	279	292
19		173	265	281	297	311	179	277	294	311	325
20		192	294	312	329	345	198	307	326	344	361
21		212	324	343	363	380	218	339	359	379	398
22		232	356	377	398	417	240	372	394	416	436
23		254	389	412	435	456	262	406	431	455	477
24		276	423	449	474	497	285	442	469	495	519
25		300	459	487	514	539	309	480	509	538	564
26		324	497	526	556	583	335	519	550	581	609
27		350	536	568	600	629	361	560	594	627	657
28		376	576	611	645	676	388	602	638	674	707
29		404	618	655	692	725	416	646	685	723	758
30		432	661	701	741	776	446	691	733	774	811
32		492	752	797	843	883					
34		555	849	900	951	997					
36		622	952	1009	1066	1118					
38		693	1061	1125	1188	1245					
40		768	1176	1246	1316	1380					

Note: All Specifications are approximate. Specifications are subject to change without notice.