

DEVELON

DL563

Bucket:2.7m³ | Rated power:162kW/2,000rpm | Rated deadweight:5,000kg



DL563

Performance characteristics



- **High reliability**

Equipped with a new generation of Weichai country four engine, power surging, efficient and reliable; With high quality transmission system, strong bearing capacity of the drive system, mature and efficient hydraulic system, energy saving and efficient at the same time to ensure excellent reliability.



- **Strong comfort**

Special silicone oil shock absorber, greatly reduce the cab vibration, and equipped with imported engine, transmission shock absorber, further reduce the vibration of the whole machine; South Korea technology stamping cab, not only good safety, sealing and sound insulation effect upgrade.



- **High flexibility**

3,200mm gold wheelbase design, flexible and efficient, small turning radius, good site adaptability, wide adaptability to working conditions.



- **Easy to maintain**

Spacious engine hood side window to ensure that all engine maintenance points are within reach; The butter filling port and transmission oil filling port are all drawn out for easy filling.

Product parameter

Rated deadweight	5,000kg	Lengthening arm unloading height	3,440mm
Rated power	162kW/2,000rpm	Wheel track	2,174mm
Wheelbase	3,200mm	Maximum unloading Angle	48°
Rated bucket capacity	2.7m ³	Maximum turning Angle	45°