DEVELON

DL667

Bucket:3.5m³ | Rated power:178kW/2,000rpm | Rated deadweight:6,400kg







Performance characteristics



High reliability

Equipped with a new generation of Weichai IV engine, surging power, efficient and reliable; Equipped with ZF electronically controlled transmission and imported hydraulic parts, the power of the entire transmission system reaches an excellent state, which ensures high reliability while saving energy and efficiency.



Strong comfort

Special steering flow amplification system and flexible limit system, with electronic control transmission, greatly reduce the control impact; Industry special silicone oil shock absorber, greatly reduce the cab vibration, imported engine, gearbox shock absorber, further reduce the vibration of the whole machine, to ensure high comfort.



Worry free after sale

Gearbox commitment 2 years /6000 hours not open box maintenance, failure to replace new gearbox; The whole machine and structural parts enjoy a long warranty period.



Easy to maintain

Spacious engine hood side window to ensure that all engine maintenance points are within reach; The butter filling port and transmission oil filling port are all drawn out for easy filling.

Product parameter

Rated deadweight	6,400kg	Lengthening arm unloading height	3,265/3,690mm
Rated power	178kW/2,000rpm	Wheel track	2,250mm
Wheelbase	3,400mm	Maximum unloading Angle	48°
Rated bucket capacity	3.5m ³	Maximum turning Angle	45°