DEVELON

DX60W ECO

Bucket:0.18m³ | Rated power:36.4kW/2,200rpm | Operating weight:5,500kg/5,800kg





Model			DX60W ECO
Boom		(mm)	3,000
Stick		(mm)	1,600
Bucket		m³	0.18
Total height [up to cabin height]	D	(mm)	2,950
Ground clearance of counterweight	G	(mm)	980
Ground clearance of engine hood	Н	(mm)	1,938
Turntable width	I	(mm)	1,850
Distance between front and rear wheels	j	(mm)	2,100
Walking width	k	(mm)	1,600
Maximum loading height	d	(mm)	4,314
Minimum excavation radius	е	(mm)	4,850




Main specifications



Hydraulic system

gine		Main pump	
and	Develon/Yanmar	Туре	Axial piston
del	DW02/4TNV94L	Maximum flow rate	138.6 Lite
intake method	Turbocharging/naturally aspirated	Fuel tank capacity	
mber of cylinders	4	Fuel tank	100L
tary system		Hydraulic oil tank	72L
ve mode	Hydraulic Drive	Antifreeze/lubricant capacity (replacement)	
e device and brak	ke	Radiator antifreeze 10L	
ering control	Steering wheel control	Engine oil	8.6L
ve mode	Hydraulic Drive	Traveling gearbox gear oil	4L
alking motor	Axial piston hydraulic motor		
erating the brake	Hydraulic brake		
Parking brake	Pilot operated mechanical braking		



www.wme.cn/develon-dx60w-eco/



		Single Wheel	Double Wheel
Operating weight	(kg)	5,560(single)	5,800(double)
Engine			
Power	(kW/rpm)	36.4/2,200	36.4/2,200
Maximum torque	(kgf.m/rpm)	20.9/1,400	20.9/1,400
System pressure	(kg/cm²)	235	235
Rotation speed	(rpm)	9.3	9.3
Walking speed	(Km/h)	23	23
Climbing ability	(%)	70	70
Tire specifications		12-16.5-12PR	7.00-15-14PR
Digging power			
Bucket	(ton)	4.5	4.5
Fore arm	(ton)	2.8	2.8
Scope of work			
Maximum excavation distance	(mm)	6,120	6,120
Maximum excavation depth	(mm)	3,450	3,498
Maximum excavation height	(mm)	6,051	6,004
Minimum turning radius	(mm)	1,650	1,650
Transport size			
Total length	(mm)	5,806	5,806
Overall width	(mm)	2,134	2,134
Overall height	(mm)	2,947	2,900
Ground clearance	(mm)	287	241
wheelbase	(mm)	2,100	2,100
Track width	(mm)	1,600	1,660

www.wme.cn/develon-dx60w-eco/