

Garbage Compactor



Key Features:

- Various size body from 10cbm to 22cbm.
- ISUZU GIGA engine, strong power; no overhaul within 2,000,000 km.
- Europe design, Electric-pneumatic control for easy operation.
- Different rear lifting system are optional.
- Steady construction, Optional 400L Sewage tank avoid second pollution.



Advantatges:



Germany SIEMENS PLC control box



Import Durable Hydraulic Valve



International 240L & 1100L bin Lifter



200L Sewage tanker prevent second pollution



ISO certified Hydraulic cylinders



Patented design with balance valve for safety



Import circuit component box



CE standard hydraulic oil pipeline

Specifications:

General	Vehicle Brand	POWERSTAR
	Chassis Brand	ISUZU
	Overall Dimension	8860 * 2500 * 2980 mm
	GVW / Kerb Weight	16,000kg / 6,750kg
Cab	Cab Capacity	3 persons allowed
	Air Conditioner	Heating/cooling air conditioner
Engine	Fuel Type	Diesel
	Engine Brand	ISUZU
	Power	350 HP (205HP, 240HP, 300HP)
	Displacement	5200ml
Chassis	Emission Standard	Euro IV or V
	Drive Type	4X2, 6x4, (left hand drive)
	Transmission	ZF 8 speed levers with 1 reverse
	Wheelbase/No. of axle	4500 mm / 2
	Tire Specification	10.00-20
	Tire Number	6 tires and 1 spare tire
	Max Speed	95 km/h
	Paint	Metallic paint
Superstructure	Body capacity	14 cbm (12-20cbm)
	Fill Hopper capacity	1.6 cbm
	Sewage tank	200L / 400L
	Filling work cycly time	20~25 s
	Discharge model	Horizontal Ejection
	Control system	Electrically Hydraulic control Manual hydraulic control
	Control panel	English or Your language
	All standard accessories: Dust bin lifter, Ladder, warning lights, Emergency stop button, handrail, fire extinguisher, basic tool kit, English manual.....	
Optional	** Back alarm and Camera can be equipped. ** Italy mulit-valve can be chosen. ** 240L (single bin or double bin) or standard 660 L, 1100 L bins with bin lifter can be choose.	

Customized Drawing:

