

Fire Truck



Key Features:

- Foam tank, Water tank, Dry powder tank volume can be optional.
- Tank material can be Carbon steel, Stainless steel or Aluminum alloy.
- All series necessary fire equipment as factory standard.
- Free training in factory if customers need.
- Original USA Darley and HALE Fire pump, Fire monitor can be optional.
- Extended model: Water fire truck, Foam fire truck, Dry powder fire truck, Forest fire truck, Water tower fire truck, Emergency rescue fire truck, Lighting tower fire truck.



Optional fire pump with control panel



Multi-function fire monitor



Different firefighting equipment meet all requirement



Durable fire hose



Multi-function fire gun optional



Water filter to keep using convenient



Optional rescue fire equipment



Aluminum firefighting ladder

Specifications:

Manufacturer	POWERSTAR TRUCKS INDUSTRY CO., LIMITED		
Product Name	Foam Fire Tender Truck ISUZU (8,000 L water+2,000L foam+1000KG powder)		
Vehicle Brand Series	ISUZU		
Vehicle Model	PT5250GXFP50		
Chassis parameters	Overall dimensions	mm	12350*2500*3500
	Gross weight	kg	25000
	Curb weight	kg	14580
	Wheel base	mm	5100+1300
	Driving type		6x4
	Number of axles		3
	Tire specification		12.00-20
	Number of Tires		10+1
Engine	Passengers in cab		2+4
	Engine model		6HK1-TCG40
	Type of fuel		Diesel
	Power/Displacement	ml	280HP /7790
	Max speed	Km/h	110
Fire performance	Emission standard(TAS)		EURO 4/
	Tank capacity		Water tank capacity: 8000 L
			Foam tank capacity: 2000 L
			Powder tank capacity: 1000 L
	Fire pump		Model: CB10/60
			Pressure (Mpa): 1.0
			Rate (L/S): 60
	Fire monitor		Model: Ps48
			Flow: 48L/S
			Water jet distance: ≥55m
			Foam jet distance: ≥50m
	Electronic alarm		LY CJB-100-C24
	Alarm lamp		LY TBD-XF-168LED

Customized Drawing:

