

35吨载重
35T PAYLOAD



40吨载重
40T PAYLOAD



LGMG CMT66A Wide Body Dump Truck

MT50

- ◆ 性能特点：适用于水泥石料厂等轻质物料的中长距离运输，具有高性价比。
- ◆ Advantage: Suitable for quarry and light material, for the middle and long distance transportation, with high cost-effectiveness.

CMT66A

- ◆ 性能特点：6x6驱动，为泥泞湿滑以及沙漠等工况设计，配置电子脱困，适应恶劣工况。
- ◆ Advantage: 6x6 drive, designed for muddy, slippery and desert working conditions, equipped with electronic escapement to adapt to harsh working conditions.

产品参数 Product Specifications

产品型号 (Model)	MT50	CMT66A
重量尺寸 (Weight&Size)		
额定载重 (Loading capacity)	35000(kg)	40000(kg)
整备质量 (Curb weight)	19500(kg)	26000(kg)
总质量 (Total weight)	54500(kg)	66000(kg)
整车尺寸 (Overall dimension)	8830×2620×3690(mm)	9160×3730×4200(mm)
发动机 (Engine)		
型号 (Model)	WEICHAI WP12G340	WEICHAI WP12G460E310
功率 (Power)	340(hp)	460(hp)
变速箱 (Transmission)		
型号 (Model)	FAST 9JSD150A / 7DS180	FAST&CAT FC6A210
车桥 (Axle)		
前后桥 (Front & Rear)	9.5+16+16(t)	18+25+25(t)
轮胎 (Tire)		
型号 (Type)	12.00R20	F: 23.5R25; R: 750/65R25
标准货箱容积 (Standard Container volume)		
平装/堆装 (Struck/Heaped)	22/25.5(m³)	21/25(m³)
性能参数 (Performance)		
最高车速空载/满载 (Max Speed Unladen/Laden)	50/50(km/h)	61/42(km/h)
最大爬坡度 (Max.Gradeability)	32%	60%
最小转弯直径 (Min.Turning Diameter)	22(m)	22(m)
最小离地间隙 (Min.Ground Clearance)	293(mm)	500(mm)