

CMTE86/CMTE106



LGMG CMTE106 Wide Body Dump Truck

CMTE86/CMTE106

- ◆ 高可靠：双电源配置，双电机系统，双制动系统，整车控制器双芯片控制。
- ◆ 管理系统：电池始终处于高效工作温度。
- ◆ 能量回收系统：下坡工况下实现制动能量回收，能耗成本相较燃油车下降6%。
- ◆ High reliability: dual power supply configuration, dual motor system, dual braking.
- ◆ Management system: The battery is always at an efficient operating temperature Energy.
- ◆ Recovery system: braking energy recovery under downhill conditions, reducing energy consumption costs by 6% compared with fuel vehicles.

产品参数 Product Specifications

产品型号 (Model)	CMTE86	CMTE106
整体性能 (Performance)		
额定载重 (Loading capacity)	60000(kg)	70000(kg)
整备质量 (Curb weight)	36600(kg)	41600(kg)
总质量 (Total weight)	96600(kg)	111600(kg)
整车尺寸 (Overall dimension)	9730×3670×4300(mm)	9970×3830×4290(mm)
电机 (Engine)	朗高 双电机210/210kw	朗高 双电机210/210kw
变速箱 (Gear Box)	綦江 2D4210	綦江 2D4210
电池容量 (Battery)	宁德 396(Kwh)	宁德 396(Kwh)
车桥 (Axle)		
前后桥 (Front & Rear)	20+35+35(t)	25+40+40(t)
车辆悬架 (Suspension)		
前后悬架 (Front & Rear)	Hydro-pneumatic/Spring	Hydro-pneumatic/Spring
轮胎 (Tire)		
型号 (Type)	14.00-25/14.00R25	16.00-25/16.00R25
标准货箱容积 (Standard Container volume)		
平装/堆装 (Struck/Heaped)	34/41(m³)	40/47(m³)
最高车速空载/满载 (Max Speed Unladen/Laden)	35/35(km/h)	35/35(km/h)
最大爬坡度(Max.Gradeability)	30%	30%
最小转弯直径(Min.Turning Diameter)	24(m)	24(m)
最小离地间隙(Min.Ground Clearance)	310(mm)	310(mm)