

性能特点 ADVANTAGE

- ◆ 系列推土机，采用集中润滑、集中测压、履带自动涨紧等先进技术，可配装多种工作装置和驾驶室可以满足各种工况的作业需求，是土石方施工、散料铲运的理想高效作业设备。
- ◆ The D22 series bulldozers adopt advanced technologies such as centralized lubrication, centralized pressure measurement and automatic track tensioning. They can be equipped with a variety of working devices and cabs to meet the operation requirements of various working conditions. They are ideal and efficient equipment for earthwork and stonework construction as well as bulk material shoveling and transporting.

产品型号 (Model)

D22

长×宽×高(mm) (不含松土器) Length × Width × Height (mm) (excluding the ripper)	5390×3735×3350
使用重量(T) (不含松土器) Operating weight (T) (excluding the ripper)	23.5
发动机型号 Engine model	NT855-C280S10
功率(kw/ r/min) Power (kw/r/min)	175/1800
最大扭矩 (N.m/rpm) Maximum torque (N.m/rpm)	1085/1300
最小燃油消耗量g/KW.h Minimum fuel consumption (g/KW.h)	205
最小转弯半径 (m) Minimum turning radius (m)	3.3
接地长度 (mm) Ground contact length (mm)	2730
铲刀型式 Blade type	直、角、U、半U (Straight, angled, U-shaped, semi-U-shaped)
铲刀长×高(mm) Blade length × height (mm)	直Straight:3735×1317 角angled:4365×1057 U (U-shaped) :3800×1345 半U (semi-U) :3725×1376
铲刀容量(m³) Blade capacity (m³)	直Straight6.4 角angled4.7 U (U-shaped) 7.5 半U (semi-U) 7.0
铲刀提升高度(mm) Blade lifting height (mm)	1210
铲刀深度(mm) Blade depth (mm)	540
铲刀最大倾斜(mm) Maximum blade tilt (mm)	直Straight>735 角angled>500 半U semi-U-shaped>755