

推土机
BULLDOZER

D32W

性能特点 ADVANTAGE

- ◆ 履带式推土机，满足国III排放要求，系采用国内领先的工艺生产技术，进行标准化量产的大功率推土机，整机采用先进的液力传动、液压操纵技术，结构先进合理，操纵轻便灵活，质量可靠。
- ◆ The D32W crawler bulldozer meets the national emission standard III requirements. It is a high-power bulldozer that is produced through standardized mass production by adopting the domestically leading production technology. The whole machine adopts advanced hydrodynamic transmission and hydraulic control technologies. It has an advanced and reasonable structure, is easy and flexible to operate, and is reliable in quality.

产品型号 (Model)

D32W

长×宽×高(mm) (不含松土器) Length × Width × Height (mm) (excluding the ripper)	6535×4150×3515
使用重量(T) (不含松土器) Operating weight (T) (excluding the ripper)	37.2
发动机型号 Engine model	NTA855-C360S10
功率(kw/ r/min) Power (kw/r/min)	257/2000
最大扭矩 (N.m/rpm) Maximum torque (N.m/rpm)	1509/1400
最小燃油消耗量g/KW.h Minimum fuel consumption (g/KW.h)	245
最小转弯半径 (m) Minimum turning radius (m)	3.9
接地长度 (mm) Ground contact length (mm)	3150
铲刀型式 Blade type	直、半U、角 (Straight, semi-U-shaped, angled)
铲刀长×高(mm) Blade length × height (mm)	直Straight:4150×1592 半Usemi-U-shaped:4150×1712 角angled:5000×1142U:4440×1740
铲刀容量(m³) Blade capacity (m³)	直10 半U11.7角6.2 U16.2
铲刀提升高度(mm) Blade lifting height (mm)	1560/1560/1703/1560
铲刀深度(mm) Blade depth (mm)	560/560/630/560
铲刀最大倾斜(mm) Maximum blade tilt (mm)	直1000 角500 半U1000 U1000