



明星产品 PX120
STAR PRODUCT PX120

优势亮点:

- ◎ 黄金动力总成
Golden powertrain
- ◎ 16L 发动机 610-770 马力，三、四阶段双排放
16L engine 610-770HP, dual emissions III & IV
- ◎ 盘式制动车桥，安全系数高
Disc brake axle, high safety factor
- ◎ 80T 级前鼓后盘式制动系统
Front drum and rear disc braking system for the 80T class
- ◎ 叶片式通风盘及耐磨摩擦片
Blade ventilation disc and wear-resisting friction plate
- ◎ 高可靠油气悬挂系统
Reliable pneumatic hydraulic suspension
- ◎ 高强度刚性车架，安全可靠
Lends high reliability oil gas suspension system
- ◎ 全液压转向系统，故障率低
Full hydraulic steering system with low fault rate
- ◎ 高强度货箱容积大，承载能力强
High strength box with large volume and loading capacity

车型 Model		PX120MT	PX120 拉煤车
尺寸 Size	外形尺寸 (mm) Overall dimension	9700×3980×4230	11200×3980×4730
	轴距 (mm) Wheel base	4050+1900	4800+1900
	货箱内尺寸 (mm) Inner dimension of box	6200×3800×2100	7700×3800×2400
	容积 (m³) Body capacity	平装 Flat: 50 / 堆装 Stack: 60	平装 Flat: 70 / 堆装 Stack: 81
重量 Weight	车辆自重 (kg) Curb Weight	40000	40000
	额定载重量 (kg) Rated load	80000	80000
	额定总重量 (kg) Rated total weight	120000	120000
	发动机型号 / 马力 Engine	玉柴 Yuchai 770HP (国 III)	玉柴 Yuchai 770HP (国 III)
性能 Performance	变速箱 Transmission	法士特 FAST 8DS260 (带缓速器 Retarder)	法士特 FAST 8DS260 (带缓速器 Retarder)
	转向机 Steering Engine	伊顿全液压 Eaton full hydraulic	伊顿全液压 Eaton full hydraulic
	前 / 后桥 Front/rear axle	蓬翔 30T 焊接前桥 / 蓬翔 45T 铸钢双级减速中后桥 PX 30T front axle/ PX45T casting dual reduction tandem axle	蓬翔 30T 焊接前桥 / 蓬翔 45T 铸钢双级减速中后桥 PX 30T front axle/ PX45T casting dual reduction tandem axle
	车架 Frame	刚性箱型车架 500×140，高 500mm，外宽 1250mm，翼板 20mm，腹板 14mm Rigid frame 500×140, height: 500mm, width:1250mm, wing plate: 20mm, web plate:14mm	刚性箱型车架 500×140，高 500mm，外宽 1250mm，翼板 18mm，腹板 14mm Rigid frame 500×140, height: 500mm, width:1250mm, wing plate: 18mm, web plate:14mm
	上装描述 Body description	高强度底板 16mm 边板 12mm，前举、海沃 Hyva 油缸、方箱 High strength plate, bottom 16mm, side 12mm, front hoisting, Hyva cylinder, square box	高强度底板 12mm 边板 10mm，前举、海沃 Hyva 油缸、方箱 High strength plate, bottom 12mm, side 10mm, front hoisting, Hyva cylinder, square box
	前中后桥板簧 Leaf spring	前悬：油气悬挂，后悬：双缸油气悬挂 Front: pneumatic, hydraulic, rear: dual pneumatic, hydraulic	前悬：油气悬挂，后悬：双缸油气悬挂 Front: pneumatic, hydraulic, rear: dual pneumatic, hydraulic
	最小离地间隙 Min ground clearance (mm)	435	435
	最小转弯半径 Min turning radius (m)	≤12	≤12
	最大爬坡能力 Max gradeability (%)	30	30
	规格 Specification	16.00R25	16.00R25
轮胎 Tire	规格 Specification	16.00R25	16.00R25