

SHACMAN H3000

OIL TANKER TRUCK



Transport type	Tanker		
Logistics type	Oil		
Distance(km)	≤300		
Road type	Paved roads		
Drive	4×2	6×4	6×4
Max weight(t)	≤20	≤40	≤50
Crusing speed/Max speed(km/h)	90	90	90
Road type	Paved roads	Paved roads	Paved roads
Loaded speed(km/h)	50 ~ 70	50 ~ 70	50 ~ 70
Vehicle model	SX5185GYML461	SX5255GYHN434	SX5315GYHR456
Engine(km/h)	WP10.270E32	WP10.300E22	WP10.340E22
Emission standard	Euro II	Euro II	Euro II
Displacement	9.7L	9.726L	9.726L
Rated Output	199kW	221kW	250kW
Max. torque	1100N·m	1390N·m	1250N·m
Transmission	RTD11509C+QH50	RTD11509C+QH50	10JSD180+QH50
Clutch	430	430	430

Frame		850×270 (8+4)	850×300 (8+5)	850×300 (8+5)
Front axle		MAN 7.5T	MAN 7.5T	MAN 7.5T
Rear axle		13T MAN double reduction5.262	13T MAN double reduction 5.262	13T STR double reduction 5.262
Tire		10.00R20	12.00R20	12.00R20
Front Suspension		Multi leaf springs	Multi leaf springs	Multi leaf springs
Rear Suspension		Multi leaf springs	Multi leaf springs	Multi leaf springs
Fuel		Diesel	Diesel	Diesel
Capacity of the fuel tank		400L (Aluminum shell)	400L (Aluminum shell)	400L (Aluminum shell)
Battery		165Ah	165Ah	165Ah
Dimensions(L×W×H)		7450×2490×3270	9275×2495×3774	11425×2490×3450
Volume (m³)		10	25	40
Wheelbase		4600	4375+1400	1800+4575+1400
Approach / Departure angle (°)		20/18	20/18	20/18
Max.gradeability(%)		34	34	34
Cab	Type	MAN H3000, lengthened flat roof		
	Equipments	◆ Rear window ◆ Manual sunroof ◆ Hydraulic driver seat with seatbelts ◆ Hydraulic suspension of cab ◆ Automated air conditioning ◆ Electric window ◆ Radio with MP3 player		
	Optional	● Air cushioned drivers seat ● Full vehicle WABCO valve ● Central locking		