

SHACMAN

H3000

TRAILER TRUCK



Transport type	Commodity transportation logistics (Standard transport)			
Logistics type	Food, fruit, wood, household appliances and other department stores			
Distance(km)	≤2000			
Road type	Paved roads			
Drive	4×2	6×4	6×4	6×4
Max weight(t)	≤50	≤70	≤55	≤90
Max speed	100	110	110	95
Loaded speed(km)	60 ~ 75	50 ~ 70	50 ~ 75	40 ~ 60
Vehicle model	SX4185HL361	SX4255HT324	SX4255HT324C	SX4255HU324
Engine	WP7.270E31	WP10.380E22	ISM 385	WP12.400E201
Emission standard	Euro II	Euro II	Euro III	Euro II
Displacement	7.14L	9.726L	10.8L	11.596L
Rated Output	199kW	280kW	283kW	294kW
Max.torque	1100N·m	1460N·m	1835N·m	1920N·m
Transmission	RTD11509C (Aluminum shell)	12JSD200T-B (Aluminum shell)	12JSD200T-B (Aluminum shell)	12JSD200T-B (Aluminum shell)
Clutch	430	430	430	430
Frame	850×270 (8+5)	850×270(8+4)	850×270(8+4)	850×300 (8+5)

Front axle	MAN 7.5T	MAN 7.5T	MAN 7.5T	MAN 7.5T
Rear axle	13T MAN double reduction 4.266	13T MAN double reduction3.866	13T MAN double reduction 3.866	13T MAN double reduction 4.266
Tire	12R22.5	12R20	12R22.5	12.00R20
Front Suspension	Little leaf springs	Little leaf springs	Little leaf springs	Little leaf springs
Rear Suspension	Little leaf springs	Little leaf springs	Little leaf springs	Little leaf springs
Fuel	Diesel	Diesel	Diesel	Diesel
Capacity of the fuel tank	400L (Aluminum shell)	400L (Aluminum shell)	400L (Aluminum shell)	600L (Aluminum shell)
Battery	165Ah	165Ah	180Ah	165Ah
Dimensions(L×W×H)	6080×2490×3560	6860×2490×3710	6860×2490×3710	6860×2490×3710
Wheelbase	3600	3175+1350	3175+1350	3175+1400
The fifth wheel	90 type (lightweight)	90 type (lightweight)	90 type (lightweight)	90 type (lightweight)
Approach / Departure angle (°)	20/66	20/66	20/66	20/66
Max.gradeability(%)	20	20	20	20
Cab	Type	MAN H3000, lengthened flat roof		
	Equipments	◆ Rear window ◆ Sun roof ◆ Four point air suspension ◆ Air cushioned drivers seat ◆ radio with Mp3 player ◆ Automated air conditioning		
	Optional	● Central locking ● Full vehicle WABCO valve		