

SHACMAN

X3000

DUMP TRUCK



Transport type	Mining engineering		
Logistics type	Ore / sand / gravel / coal		
Distance (km)	≤200		
Road type	Paved roads		
Drive	6×4	6×4	6×4
Max weight(t)	≤50	≤50	≤50
Max speed(km/h)	75	75	80
Loaded speed(km/h)	40 ~ 60	40 ~ 60	40 ~ 60
Vehicle model	SX32556T384	SX32556V384	SX32556T384C
Engine	WP12.380	WP12.420	ISM 385
Emission standard	Euro II	Euro II	Euro III
Displacement	11.596L	11.596L	10.8L
Rated Output	280kW	309kW	283kW
Max. torque	1500N·m	1750N·m	1835N·m
Transmission	10JSD160+QH50	10JSD180+QH50	12JSD180T+QH50
Clutch	430	430	430

Frame	850×300 (8+7)	850×300 (8+7)	850×300 (8+7)
Front axle	MAN 7.5T	MAN 7.5T	MAN 7.5T
Rear axle	16T MAN double reduction 5.262	16T MAN double reduction 5.262	16T MAN double reduction 5.262
Tire	12.00R20	12.00R20	12.00R20
Front Suspension	Multi leaf springs	Multi leaf springs	Multi leaf springs
Rear Suspension	Multi leaf springs	Multi leaf springs	Multi leaf springs
Fuel	Diesel	Diesel	Diesel
Capacity of the fuel tank	380L	380L	380L
Battery	165Ah	165Ah	180Ah
Dimensions(L×W×H)	7950×2490×3270	7950×2490×3270	7950×2490×3270
Trunk(L×W×H)	5600×2300×1300	5600×2300×1300	5600×2300×1300
Wheelbase	3775+1400	3775+1400	3775+1400
Approach / Departure angle (°)	28/23	28/23	28/23
Max.gradeability(%)	30	30	30
Cab	Type	X3000 , mid-lengthened flat roof	
	Equipments	◆ Rear window ◆ Automated air conditioning ◆ Hydraulic suspension of cab ◆ Hydraulic driver seat with seatbelts ◆ One sleeping bed ◆ Hydraulic reversal ◆ Radio with MP3 player	
	Optional	● Air cushioned drivers seat ● Central locking	