

SHACMAN
X3000
DUMP TRUCK



Transport type	Highway transport		
Logistics type	Ore / sand / gravel / coal		
Distance (km)	≤200		
Road type	Paved roads		
Drive	8×4	8×4	8×4
Max weight(t)	≤90	≤90	≤90
Max speed(km/h)	75	75	75
Loaded speed(km/h)	40 ~ 60	40 ~ 60	40 ~ 60
Vehicle model	SX33156T366	SX33156V366	SX33156T366C
Engine	WP12.380	WP12.420	ISM 385
Emission standard	Euro II	Euro II	Euro III
Displacement	11.596L	11.596L	10.8L
Rated Output	280kW	309kW	283kW
Max. torque	1500N·m	1750N·m	1835N·m
Transmission	10JSD160+QH50	10JSD180+QH50	12JSD180T+QH50
Clutch	430	430	430

Frame		850×300 (8+7)	850×300 (8+7)	850×300 (8+7)
Front axle		MAN 7.5T	MAN 7.5T	MAN 7.5T
Rear axle		16T MAN double reduction 5.262	16T MAN double reduction 5.262	16T MAN double reduction 5.262
Tire		12.00R20	12.00R20	12.00R20
Front Suspension		Multi leaf springs	Multi leaf springs	Multi leaf springs
Rear Suspension		Multi leaf springs	Multi leaf springs	Multi leaf springs
Fuel		Diesel	Diesel	Diesel
Capacity of the fuel tank		380L	380L	380L
Battery		165Ah	165Ah	180Ah
Dimensions(L×W×H)		9300×2490×3210	9300×2490×3210	9300×2490×3210
Trunk(L×W×H)		7400×2300×1500	7400×2300×1500	7400×2300×1500
Wheelbase		1800+3575+1400	1800+3575+1400	1800+3575+1400
Approach / Departure angle (°)		28/55	28/55	28/55
Max.gradeability(%)		25	25	25
Cab	Type	X3000 , mid-lengthened flat roof		
	Equipments	◆ Rear window ◆ Automated air conditioning ◆ Hydraulic suspension of cab ◆ Hydraulic driver seat with seatbelts ◆ One sleeping bed ◆ Hydraulic reversal ◆ Radio with MP3 player		
	Optional	● Air cushioned drivers seat ● Central locking		