

SHACMAN
X3000
LORRY TRUCK



Transport type	Complex transport	
Logistics type	Wood, building materials, steel, ceramic tile, etc.	
Distance (km)	≤500km	
Road type	Paved roads	
Drive	8×4	8×4
Max weight(t)	≤60	≤60
Crusing speed/Max speed(km/h)	90	90
Loaded speed(km/h)	50~65	50~65
Vehicle model	SX13155T456	SX13155T456C
Engine	WP12.380	ISM 385
Emission standard	Euro II	EuroIII
Displacement	11.596L	10.8L
Rated Output	280kW	283kW
Max. torque	1500N·m	1710N·m
Transmission	12JSD180T	12JSD180T
Clutch	430	430
Frame	850×300 (8+7)	850×300 (8+7)

Front axle		MAN 7.5T	MAN 7.5T
Rear axle		16T MAN double reduction 4.769	16T MAN double reduction 4.769
Tire		12.00R20	12.00R20
Front Suspension		Multi leaf springs	Multi leaf springs
Rear Suspension		Multi leaf springs	Multi leaf springs
Fuel		Diesel	Diesel
Capacity of the fuel tank		400L (Aluminum shell)	400L (Aluminum shell)
Battery		165Ah	180Ah
Dimensions(L×W×H)		11425×2490×3710	11425×2490×3710
Trunk(L×W×H)		9500×2300×800	9500×2300×800
Wheelbase		1800+4575+1400	1800+4575+1400
After the suspension		2300	2300
Approach / Departure angle (°)		18/12	18/12
Max.gradeability(%)		34	34
Cab	Type	X3000 , high roof	
	Equipments	◆ Rear window ◆ Manual sunroof ◆ Hydraulic driver seat with seatbelts ◆ Hydraulic suspension of cab ◆ Electronic air conditioning with temperature control ◆ Electric window ◆ Radio with MP3 player	
	Optional	● Air cushioned drivers seat ● Full vehicle WABCO valve ● Central locking	