



TL855  
OFF-ROAD DUMP TRUCK

To be the leading supplier of engineering transportation solution and equipment



TL855 is a kind of independent innovation product and has become a generation of industry excellence.  
TL855 has the characteristics of mature technology, stable quality, safety and reliability, and high comprehensive cost performance.  
Won No.1 market share, TL855 has won the "Market Performance Gold Award" in the industry.

TL855 off-road dump truck					
Overall parameters	Model	TL855D	Axle	Manufacturer / Country	Hande/China
	Brand	Tonly		Load/T	13+25+25
	Drive mode	6×4	Tires / Rims	Tire model	14.00-25
	GVW (t)	65		Rim size	10.0/2.0-25
	Rated payload (t)	40	Container	Base plate material/thickness (mm)	T700/16
	Kerb weight (t)	25		Rear plate material/thickness (mm)	T700/10
	Dimensions (mm)	8895×3220×3800		Front plate material/thickness (mm)	T700/10
	Wheelbase (mm)	3600+1500		Side plate material/thickness (mm)	T700/10
	Wheel track (mm)	2442/2252		Container volume (m³)	25
	Minimum ground clearance (mm)	350	Hydraulic system	Model	FC179
	Minimum turning radius (m)	10.5		Manufacturer / Country	HYVA/China
	Maximum height of bucket lift (mm)	7650		Steering device	Dual steering
	Maximum angle of bucket lift (°)	50		Lifting time (s)	23
	Loading height (mm)	3800		Discharge time (s)	23
	Braking distance (m)	12	Weight distribution	Empty load	
	Maximum climbing degree (%)	≥36		Front axle (kg)	10000
	Maximum speed (km/h)	40		Rear axle (kg)	15000
Engine	Model	WP12G430E310		Total weight (50% fuel) (kg)	25000
	Manufacturer / Country	Weichai/China		Loaded	
	Power (hp/kw)	430/316		Front axle (kg)	15000
Transmission	Model	7DS180	/	Rear axle (kg)	50000
	Manufacturer / Country	Fast/China		Total weight (kg)	65000
	Input torque (N·m)	1800		/	/